

Each assembly fabricated with solid brass quick connects featuring:

- Instant connection with visual and audible lock indicators assuring connection is securely made
- Connector attached with secure interlock crimp ferrules to prevent hose blow-out
- Brass body with stainless locking balls and EPDM seals
- Colored ID band to indicate supply or return water usage
- Full Flow Technology to minimize pressure drop
- No threaded connector to overtighten or leak
- No internal sealing washer to lose
- Hoses are 100% tested

Tube Construction: High grade EPDM hose core

Reinforcement: Single braid high strength synthetic yarn

Cover: 304 stainless steel (ASTM A580-18) outer braid

Temperature Range: -40°F to +257°F

Maximum Working Pressure: 750 psi

Minimum Burst Pressure Rating: 2250 psi



Full flow Insta-Lock™ connector



Colored ID bands to indicate supply and return water usage.



Audible lock indicator assures a connection has been made.

Behind every unit that carries the Whalen name is a singularity of purpose: the engineering and manufacturing of products that improve the quality of life for our customers.

Our long-term commitment to this endeavor assures you of systems that are distinctive in **concept**, **performance**, **reliability** and **value**.

The number of industry “firsts” from Whalen is impressive. They include:

- The industry’s first vertical stack valveless fan coils
- The first vertical stack heat pump offering
- The first removable chassis closet-type heat pumps
- The first AHRI-listed water-cooled air conditioning units with hydronic heat

Let us put Whalen innovation to work for you, too. Find out how our approach to your project will deliver a “perfect fit” solution – and make your life easier.

Need to locate a sales representative? Whalen’s sales rep locator tool was designed to help you easily find a Whalen sales representative within the United States and Canada.

whalencompany.com/relocator



P.O. Box 1390 • Easton, MD 21601 USA
whalencompany.com



WL078 rev. 01-20